

WP-BF series Premade Pouch Rotary Packaging Machine



Application

- ◎ Applicable Bag Type: four sides sealed bag, zipper bag, standup bag.
- ◎ Applicable Bag Material: a variety of laminated films, single layer PE film.
- ◎ Applicable Products: a variety of snack food, candy, bean, pet food, dried fruits, sugar, milk powder, coffee powder, etc.

Feature

- ◎ Automatically functioned by PLC system, user-friendly HMI menu page helps to easy operate.
- ◎ Equipped with cushion structure helps to running smooth and silence.
- ◎ Complete error detection like no bag alarming at opening station, product filling station, sealing station.
- ◎ The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

Technical Parameters

Model	WP-BF8200	WP-BF8260	WP-BF6320
Station No.	8 stations	8 stations	8 stations
Weighing Range	L: ≤ 350mm W: 80~220mm	L: ≤ 450mm W: 140~260mm	L: ≤ 450mm W: 200~340mm
Packing Speed	10~60 (bags/min)	10~60 (bags/min)	10~60 (bags/min)
Bag Size	L: ≤ 350mm W: 100~220mm	L: ≤ 400mm W: 140~260mm	L: ≤ 450mm W: 200~320mm

Station Function	bag feeding, date printing, bag opener, products filling, backup, backup, sealing, output		
Voltage	3KW/380V/50(60)Hz	3KW/380V/50(60)Hz	3KW/380V/50(60)Hz
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.4m ³ -0.6m ³ /min	0.4m ³ -0.6m ³ /min	0.4m ³ -0.6m ³ /min
Machine Size(mm)	1610*1510*1480	1650*1820*1580	1770*1540*1580
Machine Weight	1400Kg	1600kg	1600kg