

## *LS1200 Top Tamp Labeler (Top Tamp Labeling Machine)*



Top tamp labelers LS1200 is space-efficient. Each part of it comes in high standard. Its high quality photo-electronic sensors help to greatly improve labeling precision. Top tamp labeler LS1200 works especially great for products of high labeling precision needs, such as electronic accessories, micro-chips, cell-phone batteries, eyelash glue and pharmaceutical syrup bottles. Thus, top tamp labeling Machine provides the best labeler solutions to industries like pharmacies, cosmetics, personal care and consumer electronics.

### **Features**

1. Easy to operate without complicated manual setups.
2. Easy to switch labeling products; even by one single operating person.
3. Programmed with two operation modes: automatic and manual; Bringing flexibility to your production.
4. Integrated control buttons in one control box; providing effortless controlling experience.
5. Visualized productivity shown on the screen of the control panel; execute planned production with ease.
6. Photo-electronic eye actively detect labeling products with precision; eliminating labeling errors
7. Equipped with tamp pneumatic applicator; fulfilling labeling tasks with stability and precision; labeling on the same targeted positions repeatedly.
8. Adjustable applicator heads; allowing wide range of application.
9. Optional barcode imprinter; carrying out printing/labeling dual task in one single process.
10. Made of high quality stainless steel with an aluminum stand; Light in weight and easy for maintenance.
11. Powered by stepper motor; dispensing labels with stability.

## Specification

- Labeling Speed: Max. 6 meter/min
- Labeling Precision: +/- 0.1 mm
- Applicable Labels: Max. (W) 10 mm \* (L) 10 mm; Min. (W) 100 mm \* (L) 300 mm.
- Label Roll Diameter: Inside 75 mm; Outside 300 mm
- Power Input: 110/220 VAC; 50/60 Hz, Single phase.
- Air Requirement: 2.5 kg/cm<sup>2</sup>
- Dimensions: (L) 515 mm \* (W) 443 \* (H) 577 mm.