



## *DQL5545G+DSC4525L High Speed Automatic Box Shrink Wrap Machine*



The high speed automatic box shrink wrap machine is controlled by OMron PLC, which is more convenient to operate. Man-machine interface, only need to input item length, height, the system automatically calculate the packing length, can store a variety of solutions, intelligent design, quick and easy to change the packing size.

### **Features**

1. This machine is the upgrade from QL5545 I sealer with BS-D4520 shrink tunnel.
2. It is higher speed, can meet 35times/min.
3. The high speed automatic box shrink wrap machine is controlled by OMron PLC, which is more convenient to operate. Man-machine interface, only need to input item length, height, the system automatically calculate the packing length, can store a variety of solutions, intelligent design, quick and easy to change the packing size.
4. Code wheel detection belt running distance, before and after allowance more accurate, horizontal vertical photoelectric position without debugging, operating more simple.

## Technical Parameters

Model	DQL5545G	DSC4525L
Max. packing size(mm)	L+2H≤550,W+2H≤450,H≤130	W450*H200mm
Max. sealing size(L*W)	L550*W450 mm	/
Power	1.40KW	11.70KW
Capacity	0-35 pcs/min	
Power source	220V 50/60HZ	380V 50/60HZ
Sealing Temperature	160-240 degree centigrade depends on thickness of film and environment temperature	
Film thickness	0.015-0.10mm	
Working Air-pressure	5KG/cm <sup>2</sup>	
Film Material	POF PVC	
Weight	340 KG	260 KG
Machine size(L*W*H)	L1760*W940*H1580 mm	L1800*W703*H1260 mm