



FL-5545TBJ+SM-5030LH+4.5M All-Servo Continuous Motion Side Sealer With Shrink Tunnel



Suitable for the packing demands of the mass production in industries such like electronics, hardware, plastic, software, food, printing, pharmaceutical, floors and ceramics.

Applicable films: POF

Shrink Tunnel Technical Features

Blowing system installed below with the whole shrinking process visible through the heat-resistant window.

Conveyor speed and air volume controlled by inverters, wind hole openness and blowing direction adjustable.

Chamber can be opened, easy for cleaning and maintenance.

All Servo Continuous Motion Side Sealer Technical Features

Continuous-motion design, non-stop product feeding, cross sealing chasing in cycle, perfect packing effect in super hi-speed.

All-servo operation system, parameters computerized just by inputting product dimensions, simple and user-friendly.

Feeding system can spontaneously synchronize the speed according to the packing speed of the host machine.

Technical Parameters

Model	FL-5545TBJ	SM-5030LH	4.5M Finger Push Conveyor
Machine Dimensions (mm)	2854 X 1564 X 1348	2372 X 1035 X 1305	4500 X 550 X 1000
Tunnel Chamber Size (mm)	/	2000 X 400 X 250	/
Max Packing Size (mm) L	Length Unlimited	1800 X 400 X 250	Unlimited X 380 X 130
Max Packing Size (mm) W+H(mm)	≤400	/	/
Cross Sealing Size L/H (mm)	520/150	/	/
Capacity (pcs/m)	80~120	0-20M	/
N.W. (kg)	1100	700	120
Power (kw)	4	20	0.06
Power supply	1PH 220V 50/60Hz	3PH 220V/380V 50/60Hz	1PH 110V/220V 50/60Hz
Air pressure (kg/cm ²)	6~8	/	/
Applicable Film	POF	POF	/