

Kawach Servo

With
Multihead Combination Weigher

*It's stronger
It's Faster
It's Economical
It just works works & works...
Without tiring*

The machine is best for.....

Extruded snacks like Kurkure & Potato Chips,
Farsan, Chiwda, Namkeen, Dry Fruits,
Pulses, Grains, Tea, Sugar, Seeds, Frozen
cut vegetables etc.



Kawach Servo Machines are very high speed machines of international standards with all precision. The high end CPU motion control technology gives the highest speed up to 100 pouches/min. (Depend on product material characteristics & pouch size). All operations are handled by individual servo motor. Kawach servo machines are designed only for large scale manufacturer. These machines run at high speed with high weight accuracy & sealing intactness.

These machines are controlled by motion CPU with touch screen. These machines have many unique features. 14 Head, 16 Head or 20 Head combination multihead gives precise weight accuracy at high speed.

Kawach servo bagger comes with following combination multihead weighing systems with or without timing bucket as per customer requirement.

- 1) Japanese (Ishida or yamato).
- 2) Chinese.

Kawach Servo

With
Multihead Combination Weigher

Additional Systems

Online batch coding device
Inert gas flushing system
3 side, 4side, centre sealing, guzzeting, block bottom etc. (optional)
Batch cutting device
No material machine stop
No film machine stop
Static charge eliminator for dust free sealing
Available in GMP model for Pharmaceutical users
'D' cut or euro slot or any shape which made to carry the bags easily

SPECIFICATIONS

Filling Capacity (Range)	5 gm - 1 Kg
Output Speed	50 to 100 pouches/min (Depends on material characteristics, fill weight & pouch size)
Control	CPU motion controlled
Operation	Servo driven
Packaging Material	Laminated Film
Heating System	Hot bar induction heating
Reel Core Diameter	70 to 76 mm
Roll Holding	Pneumatic shaft
Maximum Roll Weight	60Kg
Electricity Required	420 V, 3Ph, 50Hz
Compressed Air Required	2 cfm at 6 bar pressure
Machines Weight (Approximate)	700 Kg to 1500 Kg
Dimension (Approximate)	1800 (w) x 1800 (L) x 3600 (h)
Available in Variety Of Models	5gm- 100gm, 20gm-200gm, 5gm-200gm, 100gm-500gm, 200gm-1Kg

Note : The design / specification are subject to change without notice on account of continuous improvement in product quality.

Unique & Special Features

- High end CPU motion control with touch Screen.
- Individual servo motor for each operation.
- Computer, printer & internet connectivity.
- Receipt function on touch panel.
- Built in self fault diagnosis system.
- Three level password protection for settings.
- Auto web tracking device.
- Integrated PID temperature controlled for precise temperature control.
- Very low maintenance (Almost maintenance free).
- If 'No material or no film' machine stop.
- Batch cutting device (Optional)
- All contact parts in SS-304. SS-316L on request.
- Epoxy powder coated structure.
- Weight adjustment & speed variation through touch screen.
- High density heaters for long life & minimum warm up time.
- Three sensor controlled film unwinding device.
- Operational & maintenance manual in touch screen.




Saurabh

Flexipack Systems Pvt. Ltd.

Manufacturer of Flexible Packaging Machinery & Allied Systems

Regd. Office & Factory: Plot No. 6 & 17, Gat No. 1556 / 1559,
Dehu - Alandi Road, Shelarwasti, Chikhali, Tal. Haveli, Pune - 412 114
Ph.: +91-20-27492722; 66346900, Fax.: 66346904.
Email: saurabhpackaging@hotmail.com; sales@saurabhflexipack.com
website : www.saurabhflexipack.com

Branches : Mumbai, Ahmedabad, Rajasthan, Chennai, Hyderabad, Bangalore, Kolkata, Delhi