

## *3138-N Printer Applicator with 17" Powered Unwind*



The Label-Aire® Model 3138-N Printer Applicator makes print and apply labeling easier – the 17" (432 mm) Powered Unwind configuration helps to significantly reduce downtime making your business even more profitable.

The 3138-N 17" Powered Unwind printer applicator is every bit as advanced a workhorse as the standard 3138-N and has all the same key features. Advanced features include automatic setup with multiple programmable label pages for easy change-overs to labels of different sizes, rate compensation for improved label placement accuracy, and advanced user-configurable I/O connectivity. All these handy features greatly simplify setup and change-overs. Like all 3138 models, the 3138-N 17" Powered Unwind is just as tough as it is versatile and advanced. The increased roll capacity of the large 17" (432 mm) powered unwind is perfect for high-speed, heavy duty operation. The 3138-N's rugged stainless steel and anodized aluminum construction is corrosion resistant providing long-lasting durability and maintenance-free operation in the most hostile environments. Like all Label-Aire printer applicators, the 3138-N 17" Powered Unwind is compatible with any O.E.M. printer on the market.

Put this advanced print and apply workhorse to work for you all day, every day. The Model 3138-N 17" Powered Unwind Printer Applicator is built to meticulous quality standards and designed to operate reliably under the most intense conditions.

- **17" (432 mm) powered unwind** which is geared for high-speed, heavy duty operation.
- **Automatic setup** includes multiple programmable label pages for easy change-overs to different label sizes.
- **Digital display** for remote operator control capability.
- **Flash memory** allows easy download of system software updates.
- **Rate compensation (with optional encoder)** for improved label placement accuracy.
- **Advanced I/O** for user-configurable for system output.
- **Heavy duty air cylinder** for 24/7 label application.
- **PLC outputs** for user-configurable for system output.
- **3-color light stack** warns of "end of label/ribbon" and "low ribbon". "Low label" is available.

## Specs

- **Dimensions:** Height: 33.8" (859 mm), Length: 39.9" (1013 mm), Width: 24.2" (615 mm)
- **Weight:** 190 lbs. (86 kg)
- **Standard Label Dimensions:** Label Width: Up to 7.2" (183 mm), Label Length: Up to 7" (178 mm) (Printer dependent)
- **Dispense Speed:** Up to 12" (305 mm) per second depending on printer and label size
- **Label Dispense Accuracy:** Up to +/- 1/32" (0.8 mm)
- **Electrical:** 115 Volts AC 60 Hz 3 Amps., 220 Volts AC 50 Hz optional
- **Air:** 4 cfm at 90 psi for most applications
- **Options:** All O.E.M. print engines, Label on pad detection, Dual Action Tamp (DAT) configuration\*, 90° swing tamp (Consult factory for additional options. \*Consult factory for availability.)