

APC-D902 Capping Screwing Machine



Equipped with three pairs of friction wheels, self-adjust tightness, helpful the caps surface. Wide applicability, it is simple and convenient if change bottles and caps, just, adjust some components. Equipped with human-computer interface and PLC control system, Ensure more stable operation and easier handling. Self-diagnose errors and stop working to make alarm at errors and missing bottles caps. The bottle with twisted cap, anti-cap and without aluminum foil will be removed.

Feature:

1. Strong compatibility, suitable for various sizes of cap shape, bottle shape.
2. A pair of cap dropping and wearing device suit for all kinds of bottle caps.
3. Cap unscrewing torque control, ensure the quality of the screw cap (optional)
4. Oscillating swivel wheel, strength is more suitable, greatly reduce the swivel wheel wear.
5. No bottle or cap, no work. By testing, capping screwing machine will wipe out the skew, inverse caps and caps without aluminium foil. It has the function of fault self-examining and any other check warning control functions, so it can ensure the continuity and accuracy.
6. Operate automatically, intelligently control with the last and next process, with good Harmony. Special operating person is not necessary so capping screwing machine can save labor cost.

Data sheet:

- Applicable bottle shape: round, oblate, square, flat square bottle
- Production capacity: 50~120 bottles per minute
- Power supply: AC220V 50Hz1.8kw
- Air pressure: 0.6Mpa
- Overall dimension: 1850×600×1560mm
- Weight: 600kg