

QUALIPAK

Plastic Ampoule Filling Sealing Machine



This machine is suitable for the unit close of medicine, drinks, dairy products, health products, food, cosmetics, perfumes, agricultural medicine, fruit purees, etc.

Features

- A. HC high speed and high precision high-end motion controller, stepless frequency control of motor speed control, servo motor control tensile membrane devices.
- B. The man-machine interface, device, operation is simple.
- C. Automatic discharge volume, a roll of film cutting, can be folded in half, there are positive and negative photoelectric pattern of version of the function. Products elegant, meet high standards of packaging requirements.
- D. Adopting electronic peristaltic pump device, and mechanical pump piston pump control. Adjustment is convenient. Filling accuracy is correct.
- E. Filling does not drip, no bubble, no overflow.
- F. Parts in contact with the medicine with high quality stainless steel 316L, machinery casings are all SUS 304 stainless steel, In line with the GMP standard.
- G. Saving films
- H. Machines can fission, convenient transportation and easy into the workshop.

Technical Data:

Filling needles	5 heads
Max forming depth	12mm
Cutting frequency	1-25 Times
Film materials	PVC/PE etc(0.2-0.4)×240mm
Capacity	6000 bottles per hour
Filling range	1-50ml
Installed power	6.5kw
Voltage	220v or 380v/50Hz (up to client's request)
Weight(kg)	1200kg
Outer Size L×W×H(mm)	3200×850×1400(mm)