



DZP-250B(C)/400B(C)/600B(C) Automatic High Speed Flow Wrapping Machine



The machine is mainly applied to the packaging of biscuit, betel nut, snowy biscuit, snowy ice-lolly, yolk pie, instant noodles, chocolate, candy, western snacks, tableware for aerial food, transparent soap, hotel articles, wet tower, gauze mask, IC card, cartoon card, electric components, trademark, little hardware etc. block-shaped things in the industries such as food, daily chemistry, cosmetics, hardware, electronics etc. It has the function of anti-moisture, dustproof and photonegative, and also enhances the product level and additional value. It can save more than 20% cost than using the manual packaging, and it can combine the aluminum plastic packaging machine and thermal contraction-packaging machine to manufacture.

Main Feature:

1. Compact structure, stable and advanced performance, easy for operation.
2. Double frequency convert motor, and stepless variable speed, and the length of bag can be set on PLC, and cutting will be reaction instant, just one step, and save the time and film.
3. PLC control, friendly operate interface, for convenient and rapid to set parameters.
4. Intelligence software, diagnose and show fault automatically.
5. Hi-sensitive electric eye, which trace the printed web on film and make the sealing on accurate position.
6. Accurate temperature control, which is control the sealing temperature for various of packing film. And the sealing effect is very well.
7. Main body is made in stainless steel. Fit to GMP standard.
8. Simple transmission system, which is more reliable work and convenient maintenance.
9. According to the situation of packaging products, it can be combined with different automatic feeder.

Model	DZP-250B(C)	DZP-400B(C)	DZP-600B(C)
Production capacity	30-230 (package/minute)		30-150(package/minute)
Packaging size (two cutters)	L (60-190) *W (30-110) *H (5-40) mm	L (60-190) *W (30-180) *H (5-60) mm	L(120-400)*W(60-260)*H (5-120) mm
Packaging size (one cutters)	L (120-190) *W (30-110) *H (5-60) mm	L (120-380) *W (30-180) *H (5-80) mm	
Maximun width of film	250mm	400mm	600mm
Power of supply	AC220V 50HZ 2.4KW	AC220V 50HZ.65KW	AC220V 50HZ 3.5KW
Weight	700kg	800kg	1000kg
Outline dimensions	4050*650*1550mm	4200*800*1550mm	5200*1000*1800mm