

JY-900 Automatic Inverted Flow Wrapping Machine



Main performance & characteristics

1. Adopt a higher precision Servo system, with PLC, Touch screen, AC inverter intelligent and step-less controlling which can realize simple operation and more correctly cutting.
2. High-sensitive photo sensor, automatically adjust, track, find cutting point, accumulatively count packs, Automatic measure bag length.
3. Digital and independent PID temperature controlling suitable for various packing materials. New type double fin sealing design makes the packaging high efficiency and beauty.
4. Adjustable bag former and pitches, enable the change of packing products conveniently.
5. The area connect to products are full stainless steel. With timing belt transmission, Compact structure, lower noise and less shake.
6. Variety of optional device is available, Like: Touch screen/Date coder/Labels applicator/Euro slot or hole punch/Gusset forming /Nitrogen or gas inflation/Spraying alcohol/Automatic film splicer/Auto feeding/Desiccant feeder /Auto falling/Products conveyor/No products no packing etc.

Using range

Mainly used for various kinds of solid objects with big sizes: such as: cookies, bread, pizza and cake bases, instant noodles, toilet paper, sanitary towel, baby diaper, fabric, infusion bag, pipe and fittings, lamps and lanterns, Industrial parts, pharmaceuticals tools, daily necessities, hardware, or any other big sizes products loaded in box or tray.

Technical parameter

Model	JY-900
Packing speed (bag/minute)	20-80bag/min
Packing size (mm)	L150-520
Length x Width x Height	W10-350
	H15-0/60-100
Maximum width of film (mm)	<320mm
Thickness of film (mm)	> 0.025mm
Power	220V,50/60HZ,4.0KW
Overall size (mm)	5000*1400*1750mm
Weight	1300kg
Package	7.5CBM.2CASES
Packing material	OPP/PP、OPP/CPP、PT/PE、PE、KOP/CPP、PT/PE/、OPP/PP、OPP/CPP、PT/PE、PE、KOP/CPP、PT/PE/、AL/PE etc. Any heat-sealable composite materials foil/film