



Tube Filling & Sealing Machinery TK850-HA



Machine Advantage

The TK850-HA modal unit adapts mechanical and strengthened assemblies, productions made smooth, production speed optimal and a high filling accuracy. Filling complies with cGMP standards. Easy change over of parts for varying tube dimensions.

Machine Specification

- Production** MAX. 60 tubes/min ; according to filling volume and mass specifications
- Tube Range** Tube diameter ϕ 10 ~ 52 mm; ; Tube + Cap : 50 ~ 280mm
- Filling volume** 2 ~ 320 ml
- Filling Accuracy** \pm 0.5% (Ext 100ml)
- Operational system** Adjustable 20 ~ 60 cycles/minute
- Electrical Requirements** Depends on Customer Specification. Main Motor 2 HP (1.5KW)
- Weight** Net.850kg / Gr.1100kg
- Crated Dimensions** 2.0M(L) x 1.7(L) x 1.9(H)
- Air Pressure** 6 bar
- Air Consumption** 800 L/min
- Operator** 1 Person

Applicable Coverage

Pharmaceutical Ointments, Hair Color Cream...

Cosmetics Face Wash, Lotion, Facial Mask, Lip Gloss...

Chemical Toothpaste, Silicone...

Food Chocolate, Mustard...

Tube Materials Plastic Tubes & Laminated Tubes

Filling Range Low, medium and High Viscosity Product Scopes

Trimming Styles

