

## PT-Z-series Ketchup Filling Machine



This is our new servo piston filling machine. Ketchup filling machine has reached the international advanced level, partial has exceeded the similar product. It is also suitable for the filling of daily chemicals, oil liquid, sauce, detergent liquid, cosmetics, medicinal liquid and flammable and explosive liquid. The ketchup filling machine adopts PLC and touch screen control panel for control material. Ketchup filling machine is characterized by accurate measuring, advanced structure, stable operating, low noise, large adjusting range, fast filling speed. Operators adjust and meter figure in the touch screen control panel, also can adjust metering of each filling head. The external surface of this tomato sauce filling machine is made of excellent stainless steel. Good appearance, applied to GMP standard.

### FEATURES

- ✓ Quantitative filling, adjustment for one key in the ketchup filling machine.
- ✓ Fast interface easy to be dismantled easy to wash, no drip, diving filling. The internal adjustment of the tomato sauce filling machine is simple. Short adjustment time for replacing bottle shape.
- ✓ No blind angle three-way valve, long service life.

### TECHNICAL PARAMETERS

Type	Head	Suitable bottles	Speed	Precise	Machine Size	Power	Power Supply	Air
PT-Z-20S	20		500ml≤5000BPH	≤0.1%	2800*1300*2350	3.5KW	AC 220/380V; 50/60HZ	0.6- 0.8Mpa
PT-Z-16S	16		500ml≤4000BPH		2800*1300*2350	3.5KW		
PT-Z-12S	12	Customized	500ml≤3000BPH		2400*1300*2350	3KW	(Customize)	
PT-Z-8S	8		500ml≤2500BPH		2000*1300*2350	3KW		
PT-Z-6S	6		500ml≤1600BPH		2000*1300*2350	3KW		