

## *Double Sides Labeling Machine YY-LG300*



### **Product introduction:**

It is intended mainly for sticking label outside the side face of round or quadrate bottles. The machine works stably and reliably, which leads to smooth labels, clearly printed dates and batch numbers (the printer allows three rows of characters). This machine is provided with a multiple control system, which assures automatic stop at the lacking or breaking of labels as well as at the lacking of bottles. This product conforms to the specifications of GMP absolutely. Which is widely used in pharmaceutical, foods and chemical industries

Mark: some equipment have no coding machine

### **Applicable bottle types**

Two sides labeling machine (non –dry type) is our company's new product, apply to square bottle, flat bottle, square bottle of food, medicine, chemical, and other industry.

### **Feature**

- 1) This machine adopts PLC control system. So the machine operation is more stable and high speed.
- 2) Operation system adopts humanized touch screen, easy to operate.
- 3) Choose the servo motor imported to prove the speed and accuracy.
- 4) Machine frame and parts are 304 stainless steel.
- 5) No bottle no label, and no label missing, no labeling blocking, has alarm
- 6) In advance function, easy to operation, compact structure.
- 7) Easy to Exchange bottle. Do not need exchange any parts.
- 8) Electrical appliance imported, stable performance. Reduce the failure rate.
- 9) Not only Suitable for single, but also production line.

**Technical Specification:**

<b>Model</b>	<b>YY-LG300</b>
Driving way	Servo system
Operation direction	According to client requirement (left or right)
Output labeling speed (B/H)	2000-18000 (according to bottle size and label size)
Accuracy	±1.0mm (as per bottle shape)
Apply to labeling	Sticker, paper
Labeling internal diameter (mm)	76mm
Labeling outer diameter (mm)	380mm
Apply to bottle diameter (mm)	25-120mm
Apply to bottle high (mm)	30-180mm
Apply to labeling size	High 15-100mm length 20-300mm
Weight (kg)	175
Power (w)	1000W
Voltage	AC220V 50/60HZ single phase
Dimension (mm)	2800 (L) ×1700 (W) ×1550 (H) mm