

Coating Machine 12"- 72"



Salient Features: Coating Pan is engineered to the perfection from SS 304 (SS 316 optional). Totally enclosed machine drive and hot air blowing system. 30", 36", 42" or 48" Coating Machine has variable speed drive. Hot air blowing system is separate. 60" or 72" Coating Machine has two speeds with step pulley without hot air blowing system. Hot air blowing system is with temperature control probe.

Salient Features:

- Coating Pan is engineered to the perfection from SS 304 (SS 316 optional).
- Totally enclosed machine drive and hot air blowing system.
- 30", 36", 42" or 48" Coating Machine has variable speed drive. Hot air blowing system is separate.
- 60" or 72" Coating Machine has two speeds with step pulley without hot air blowing system.
- Hot air blowing system is with temperature control probe.

Technical Specifications:

MODEL	12"	18"	24"	30"	36"	42"	48"	60"	72"
Loading	5	7	20	40	60	90	110	150	200
Capacity in Kg.		to 8	to 25	to 45	to 80	to 100	to 120	to 210	to 250
Motor HP	0.5	0.5	1.0	1.5	1.5	2.0	2.0	5.0	7.5
Blower HP	0.25	0.25	0.5	0.5	1.0	1.0	1.0	2.0	2.0
Blower fan Volume CFM	90	90	150	150	150	150	150	300	300
Heater Capacity in KW	1.0	1.0	3.0	3.0	3.0	3.0	3.0	5.0	5.0