

# HESLY

## Packaging Line DZH-120P and BT-400C-I



This machine is suitable for automatic feeding bottle (round, square bottle) into carton (either for blister or bottle). On line bottle unscramble and feeding, leaflet fold (1-4 folds) and feeding, carton opening and forming, products and leaflet pushing into carton, printing batch number, sealing carton with tuck-in or hot melt glue device. Automatically reject lacking of leaflet or product and finished product out.

### Features:

1. International famous brand of electrical component such as PLC touch screen, frequency inverter, etc.
2. Adopt human-machine operation system.
3. Automatically stop when machine is overload.
4. Automatically reject lacking of package product and leaflet.
5. Automatically display trouble, Alarm and count finished products.
6. Stable performance, operation is easy.

### Main Technical Parameters:

tem	Parameters	
Encasing speed	35-120cartons /min	
Box	Quality requirement	250-350g/m <sup>2</sup> [Base on carton size]
	Dimension of carton(L×W×H)	(65-200)×(30-85)×((8-50)mm
Compressed air	Working pressure	≥0.6mpa
	Air consumption	120-160L/min
Power supply	380v 50HZ	
Main motor power	1.6kw	
Machine body dimension (L×W×H)	3400×1140mm×1800mm	
Machine weight	1200kg	

**BT-400C-I Overwrapper:**

<b>SIZE RANGE (IN MM)</b>	<b>MIN. STANDARD</b>	<b>MAX. STANDARD</b>
Length (L)	10	300
Width (W)	50	200
Height (H)	20	80
Maximum output *	30strokes per minute	
Film width	60-400MM	
Voltage	220V 50HZ ,ONE PHASE	
Power	4KW	
N.weight	1000Kg	
Film-roll diameter max.	320 mm	
Packaging material	Polypropylene,Bopp	
Basic configuration	HOPPER INFEED	
OVERWRALL DIMENSION	2200X935X1960MM	
Conveyor belt	1800x500x150mm	
Optional accessories	printmark registration, Date printer	
* depending on product, machine configuration and packaging material		