



## BG-Series of High-efficient Film Coating Machine



This machine is adopted with novel micro-computer PLC and temperature Model control system, touching screen to display, ease of operation, high efficiency and saving energy, cleaning and safety, accord with the requirement of GMP, it is widely used in pharmacy as well as foodstuff industry, and it is an ideal equipment for tablet, pill, candy, chocolate etc to make solvent film coating, organic film co-acting, sugar coating.

### Main technical parameters:

TYPE	BG-150D	BG-80D	BG-40D
Max.Capacity(Kg)	150	80	40
Power of Main Unit(Kw)	2.2	1.5	1.1
Speed of Drum(rpm)	2-20	3-24	3-28
Weight of Main Unit(Kg)	900	750	550
Overall Dimensions of Main Unit(LxWxH)mm	1750x320x2020	1390x1050x1720	1180x850x1520
Power of High Efficiency Filtering Air Heater(Kw)	2.2	1.5	1.1
Overall Dimensions of High Efficiency Filtering Air Heater(LxWxH)mm	1080x820x2500	950x800x2080	810x700x1720
Weight of High Efficiency Filtering Air Heater(Kg)	400	350	300
Power of Dust cleaning Air exhauster(Kg)	5.5	3	2.2
Overall Dimension of Dust Cleaning Air Exhauster(LxWxH)mm	1060x1100x2100	900x800x1900	730x730x1660
Weight of Dust cleaning Air Exhauster(Kg)	500	350	300
Power of Heat-insulating Steam and Electrothermal Dual-purpose Agitator(Kw)	6	6	4