

Shampoo Filling Machine



Our automatic linear structure shampoo filling machine adopts the principle of plunger quantitative filling, bottle feeding, positioning and filling, the bottle is automatically controlled by PLC, which conforms to the GMP standard. It is suitable for liquid filling of medicine, food, daily chemical, pesticide, fine chemical industry, etc.

Description

Rito machinery company's shampoo filling machine adopts the principle of plunger quantitative filling, bottle feeding, positioning and filling, the bottle is automatically controlled by PLC, which conforms to the GMP standard. It is suitable for liquid filling of medicine, food, daily chemical, pesticide, fine chemical industry, etc.

Feature:

1. Touch screen operation interface;
2. The up and down movement type filling can effectively prevent the generation of foam and is easy to disassemble and wash;
3. The filling accuracy can reach $\pm 1\%$;
4. Grounding cylinder, unique grounding valve design, no leakage;
5. With no bottle, no flash, automatic bottle stop function;
6. Design different positioning devices according to the actual situation of the bottle;
7. The equipment is easy to clean, it can be disassembled without tools, and it can also be cleaned online or at high temperature

Sterilization

8. PLC programmable control adopts Japan's Mitsubishi;
9. The frequency converter adopts French Schneider;
10. The pneumatic components adopt Taiwan Airtac;

11. Material contact parts are made of SUS304# stainless steel;

12. The equipment meets health and safety standards. The user can choose the glass protective cover.

Machine Parameters:

Automatic Bottle Filling Capping and Labeling Machine	
Name	bottle filling machinery production line
	bottle filling capping and labeling machine
	shampoo filling machine
Filling volume	100-1000ml,500-5000ml;
Filling Heads	1—12
Capacity	2000-3500 bottles/hour
Control system	PLC+ Touch screen
Precision	±0.5-1.0%
Bottle height	80-370 mm (adjustable)
Voltage	AC220V or AC 380V
Power	2.0-3.5Kw.
Pneumatic	0.35cbm/min, 0.6-0.8Mpa
Dimension	2400*1100*2250mm
G.W.	900-1200Kg.
Auxiliary equipments	Auto bottles feeder, auto capping machine, auto induction sealing machine,
	auto labelling machine, shrink labelling machine,
	ink-jet printer, auto carton packing machine,etc.