



## *Automatic Tube Filling Sealing Machine HNRG-60A*



This product is our company to introduce foreign advanced technology, combined with the requirements of the GMP optimization design and development of successful high-tech equipment. With a reasonable structure, functional integration, convenient operation.

### **Features**

1. High grade liquid crystal display programming controller and button combination operation screen, a comprehensive grasp of speed, parameters of the equipment and production count statistics, pneumatic equipment instructions, fault display operation status, the operation is simple and user-friendly.
2. Feed tube, photocell, inert body temperature (optional), filling, sealing, printing, finished the whole products automatic.
3. High accuracy photocell system, to reduce the mistake sealing of tube body color.
4. Adjusting the position of the external, digital display, adjust fast and accurate (applicable to multi specification, multi variety production).
5. Machine, light, electricity, gas integration, no tube no filling, for the pipe is not in place, low pressure, automatic display (alarm); open the protective door can automatically shut down, such as automatic functions.
6. Has nine stations, full function, convenient for variety, metal pipe, plastic pipe, composite pipe mould can be interchangeable, suitable for any folding metal tube.

## Technical parameter

<b>Model</b>	<b>HNRG-60A</b>
<b>Voltage</b>	AC220V/50HZ (380V)
<b>Filling Range</b>	60-250ml
<b>Working Speed</b>	40-45times/Min
<b>Filling Accuracy</b>	±1%
<b>Weight</b>	1000kg
<b>Tube Diameter</b>	10-50mm
<b>Tube length</b>	80-250mm
<b>Air Pressure</b>	0.55-0.65MPA 0.1m <sup>3</sup> /min
<b>Hot Sealing Power</b>	3KW
<b>Machine Size</b>	2620*1020*1980