

DZP-250F/400F Flow Wrapping Machine



The is mainly applied to the packaging of biscuit, betel nut, snowy biscuit, snowy ice-lolly, yolk pie, instant noodles, chocolate, candy, western snacks, tableware for aerial food, transparent soap, hotel articles, wet tower, gauze mask, IC card, cartoon card, electric components, trademark, little hardware etc. block-shaped things in the industries such as food, daily chemistry, cosmetics, hardware, electronics etc. It has the function of anti-moisture, dustproof and photonegative, and also enhances the product level and additional value. It can save more than 20% cost than using the manual packaging, and it can combine the aluminum plastic packaging machine and thermal contraction-packaging machine to manufacture.

Main Feature:

1. Double frequency inverter control with steeples variable speed. Just in one step, the length of bag can be set and cut at any time without the need to adjust trail operation, and it is time saving and film saving.
2. It adopts international famous electric components, PLC control, friendly interface, with convenient and rapid setting of parameters.
3. The indication of fault is clear, and the function is more humanized.
4. Highly sensitive electric-eye color code tracking can make the sealing position be more accurate.
5. The accurate temperature setting is suitable for various of packaging material and improve the quality of seal.
6. It have functions of positioning power-off, without sticking to the blade and without waste of film.
7. Simple and clear driving system with more reliable work and more convenient maintenance.
8. The controls are operated on software, which facilitates the function regulation and technology upgrade so as to satisfy the production requirement.
9. It can be allocated with labeling device for automatic production.
10. The machine can be combined with the large transfusion production line, not required manual adjustment.

Model:	DZP-250F	DZP-400F
Packing capacity	30-230 Package/minute	
Bag size (mm)	L(60-190)xW(30-110)xH(5-40) mm	L(60-190)xW(30-180)xH(5-60)mm
Max. width of film	250mm	400mm
Power supply	AC220V 50Hz, 2.4KW	AC220V 50Hz, 2.65KW
Weight	700kg	800kg
Overall dimension (LxWxH,mm)	3350x1800x650mm	3500x1800x800mm