



Horizontal Custom Popsicle Wrapping Sealing Machine CK-ZS350W



The horizontal popsicle wrapping machine is specially designed for the packaging of some bulk, soft, long strip materials without distinguishing between the positive and negative sides. The longitudinal sealing device is on the upper part of the package, which can alleviate the influence of heat sealing on the package.

In addition, we also launched some new models of the popsicle sealing machine that can solve the problem of package automation for customers, eliminating the need for pallets and saving a lot of costs.

Popsicle Wrapping Machine Features:

1. The main control uses PLC program control, stable performance, simple operation.
2. The main motor is equipped with high quality ac inverter to realize stepless transmission.
3. High-precision photoelectric detection and tracking, two-way automatic compensation, accurate and reliable.
4. The belt length is adjusted by the toothed chain CVT, which is durable, stable and accurate.
5. No manual setting is needed for bag length, which is automatically detected and set during equipment operation. And this popsicle wrapping machine can make different types of bags.

Custom Popsicle Packaging Machine Principles and Features:

- © Special adjustable bag-making device can better meet the requirements of multiple varieties and specifications.
- © The differential feeding mode makes it convenient to adjust the feeding position in the running process.

© Advanced microcomputer packaging controller, excellent man-machine dialogue mode, so that the speed, the length of the bag, the location of the cut can be directly displayed on the interface.

Popsicle Wrapping Machine Scope of Application:

The popsicle sealing machine is suitable for food (instant noodles, bread, hamburger, biscuits, ice cream, etc.), daily necessities (soap, napkin, etc.).

Automatic Popsicle Wrapping Machine Optional Device:

- Code printer
- Straight line middle sealing wheel
- Net end sealing die
- Super touch screen

Type	CK-ZS350W
Film width	Max.350mm
Bag length	110-330mm
Bag width	30~130mm
Product height	10-60mm
Film roll diameter	Max. 320mm
Packaging rate	30-120bag/min
Power	220V,50/60Hz,2.4KW
Machine size	(L)3670×(W)820×(H)1410
Machine quality	800Kg