



Automatic Tube Filling & Sealing Machinery TK850-HAO



Machine Advantage

The TK850-HAO modal unit adapts mechanical and strengthened assemblies, productions made smooth, production speed optimal and a high filling accuracy. Filling complies with cGMP standards. Suit for Oval tube and circle tube, can use both tubes at the same time, easy simple operating. It doesn't necessary to change the parts.

Machine Specification

- Production** MAX. 60 tubes/min ; according to filling volume and mass specifications
- Tube Range** Tube diameter $\phi 10 \sim 52$ mm; Tube + Cap : 50 ~ 280 mm
- Filling Volume** 2 ~ 320 ml Filling Accuracy ± 0.5 % (Ext 100 ml)
- Operational system** Adjustable 20 ~ 60 cycles/minute
- Electrical Requirements** Depends on Customer Specification. Main Motor 2 HP (1.5KW)
- Weight** Net. 850kg / Gr.1100kg
- Crated Dimensions** 2.0M(L) x 1.7M(W) x 1.9M(H)
- Air Pressure** 6 bar
- Air Consumption** 800 L/min
- Operator** 1 Person

Applicable Coverage

Pharmaceutical Ointments, Hair Color Cream...

Cosmetics Face Wash, Lotion, Facial Mask, Lip Gloss...

Chemical Toothpaste, Silicone...

Food Chocolate, Mustard...

Tube Materials Plastic Tubes & Laminated Tubes

Filling Range Low, medium and High Viscosity Product Scopes

Trimming Styles

