



HDS-2500/4500/6000 High Speed Automatic Packing Machine



This is a product of Urban food packaging production line, which adopts a number of production patents, including high speed American imported smart chip of the United States, with high measurement accuracy.

This product is suitable for a variety of fields, including aviation tableware, restaurant tableware, etc

Features:

1. Control circuit uses high speed American imported smart chip, measurement precision, and with a touch- screen display, electrical fault auto-detection, simple operation, easy adjustment .
2. Mechanical formula function (memory function: reserving have been debugged procedure), avoid that multiple packaging similar specification products may make it debugging repeatedly, wasting material, saving more time to improve packing efficiency.
3. Wet tissue folding machinery and packaging machinery can isolated operation (both of one is closing, another one also can running any time)
4. Touch screen control tissue feeding, not adjust by machine.
5. Using high-quality dual-frequency simple mechanical structure, easy maintenance, long life, less wear and tear.
6. High-precision photoelectric detection tracking, bi-directional automatic compensation, accurate and reliable.
7. Bag length without manual configuration, auto-detection equipment operation, automatically set.
8. Packing speed and bag length of the dual inverter control, stepless variable speed, arbitrary adjustment range, with the former working procedure of production line a perfect match.

Specifications:

Machine Model	HDS-2500	HDS-4500	HDS-6000
Packing Type	Trilateral closure H	Trilateral closure H	Trilateral closure H
Packaging Film Thickness	0.018-0.06mm 18-60Micorn	0.018-0.06mm 18-60Micorn	0.018-0.06mm 18-60Micorn
Max Film Width	230mm	420mm	550mm
Bag Length	90-330mm	120-550mm	150-600mm
Packaging Width	30-100mm	80-180mm	150-260mm
Packaging Height	≤35mm	≤95mm	≤95mm
Max. speed	200bag/min	120bag/min	120bag/min
Voltage/Total Power	220V/2.8kw	220V/3kw	220V/3kw
Dimension	4200*800*1300mm	4200*900*1300mm	4200*1000*1300mm
Weight	500kg	600kg	700kg