

ATM-L520VW Fully Auto High Speed Weighing Packing Machine with Combination Weigher



Technical characteristics:

1. English and Chinese screen display, operation is simple.
2. PLC computer system, function is more stable, adjustment any parameters not need stop machine.
3. It can stock ten dispose, simple to change variety.
4. Sever motor drawing film, position accurately.
5. Temperature independent control system, precision get to $\pm 1^{\circ}\text{C}$.
6. Horizontal, vertical temperature control, suitable for various of complex film, PE film packing material.
7. Packing type diversification, pillow sealing, standing type, punching etc.
8. Bag-making, sealing, packing, print date in one operation.
9. Work circumstance quiet, low noise.
10. 4 sets of servo system (Panasonic brand) with continuous pulling film system, for pulling film, horizontal sealing jaws, the horizontal sealing system up, vertical sealing system and horizontal system up-down moving.

Application:

Suitable for packaging many different kinds of products; such as puffy food, shrimp roll, peanut, popcorn, cornmeal, dried fruit, seed, small hardware, dumplings, vegetable, fruits and Sugar etc. which shape is roll, slice and granule.

Technical Parameters:

Model No.	ATM-L520VW
Packing speed (bags/min)	10-150bags/min
Max width of packing film (mm)	140mm-520mm
Packing pouch size(mm)	(L): 50-400mm (W): 60-250mm
Total power (kw)	4.8Kw
Filling range(ml)	150-1000ml
Max outside diameter of rolling film (mm)	≤φ400
Type of bag making	Pillow bag/gusset bag
Air consumption	0.8Mps 0.3m ³ /min
Packing film thickness(mm)	0.05-0.12
Gross weight(kg)	550Kgs
Machine dimension(mm)	(L)1315×(W)1023×(H)1343mm
Working voltage	220v 50hz
Packing film material	BOPP/CPP, BOPP/VMCP, BOPP/PE, PET/VMPET/PE, PET/PE, ect