


NY-822B Position Round Bottle Labeling Machine



NY-822B Positional Stand Up Round Rotary Bottle Labeling Machine to label on the circumference of surface or other curved surface for food glass pet plastic round bottles, jars, cans, tins etc. It has optional circumference positioning detection device, realize the specified position single or double sticker labeling.

Features:

1. Have positioning function at your options. Also can realize one sticker or two stickers labeling mode.
2. The labeling head convenient to adjust, the labeling speed is automatically synchronous with the conveyor belt speed to ensure precise labeling.
3. The speed of conveyor line, the speed of pressure belt and the speed of label output can be set and changed by the PLC human interface.
4. Use famous brand PLC, stepping or servo motor, driver, sensor, etc, good quality components' configuration.

Introduction:

1. Different labeling solutions for flat surface, round labeling, taper wrapping labeling can be supplied. One product can accomplish one sticker, two stickers or more stickers labeling, also can one sticker to finish one side, two sides, three sides or more sides labeling.
2. We can supply you the optional bottle unscrambler turning table, which can be connected directly before the labeling machine, the operators can put the bottles on the rotary table, then the rotary table will send the bottles to the labeling machine to the labeling machine automatically.
3. It also can match with weight checker, metal detector, bottle filling machine, capping machine, can seaming machine, cover impressing machine, inkjet /laser / TTO printer etc.

Technology Data:

Model	NY-822B
Labeling Precision	±1mm (excluding product and label error);
Power Supply	AC220V 50/60Hz 700W
Conveyor Speed	5~25 meters/minute;
Labeling Speed	10~35pcs/min(Related to product, label size);
Sticker Out-Come Speed	Stepping Motor: 5~19 meters/minute
	Servo Motor: 5~25 meters/minute
Application Bottle Size	External diameter: Φ25-100mm;
	Height: 25mm~300mm;
Applicable label size	Label Length: 20mm~290mm;
	Label Width(body paper width): 20mm~120mm; 180mm (option)
Inner dia. of paper roll	Φ76mm
External dia. of paper roll	Max. Φ300mm
Size (LXWXH)	2000mm×1150mm×1500mm
Weight	185kgs