



## ***Link-40H18 Fully Automatic Stainless Steel Case Carton Box Opening Erecting Unpacking Machine***



Link-40H18 automatic box unpacking machine adopts international advanced technology manufacturing, and selects imported parts, electrical components and pneumatic components; With more than 10 years of independent research and development in the field of unpacking machine technical experience, and the introduction and absorption of Japan, Germany in the field of unpacking machine advanced technology.

Automatic unpacking machine Link-40H18 is stable and reliable, with international high quality. Parts through the aging test, to ensure that every detail is more stable. It is suitable for unpacking and sealing of various sizes of cartons. If you need to change the specifications of cartons, you can adjust them manually. The operation is simple and convenient.

Automatic unpacking machine adopts PLC+ man-machine interface control, easy to operate, simple maintenance, stable performance, is an essential assembly line equipment for automatic large-scale production. Durable performance, tight structure design, no vibration during operation, stable and reliable operation; Equipped with blade protection device to avoid accidental stabbing during operation; Add protective cover, make production more safe, more good packaging. Folding does not stay, folding and sealing is completed in the delivery of the unpacking machine; 3 seconds to complete the box suction, molding, folding, sealing the whole process; High speed, stable, convenient and economical.

The successful development of Link-40H18 automatic carton unpacking machine fills the vacancy of the domestic vertical automatic carton unpacking machine in the unpacking capacity of 14-18 boxes/min; Low price, high efficiency, cost-effective. Better meet the needs of new and old customers. Since the success of research and development, has been widely used in food, medicine, beverage, tobacco, daily chemicals, electronics and other industries.

**Technical Parameters:**

<b>Model</b>	<b>Link-40H18</b>
The power supply	220V/ 50Hz / 0.4KW
Working air pressure/air consumption	6kgf /cm <sup>2</sup> 450nl/ min
Packing specification	280≤L≤480;160≤W≤350;130≤H≤400;410≤L+W≤910;300≤W+H/2≤620mm
Out of the way	Vertical molding
Countertop height	650mm
The belt speed	13~16 boxes/min
Packing tape	BOPP/PVC
Tape size	W48mm 58mm 72mm
Installation dimensions	L 2500 * W 1950 * 1450mm
The net weight	550Kg