



Automatic Powder Filler Machine DH-L1-S(M)



Auger fillers are suitable for filling free-flowing and non-free-flowing powders accurately. They use a rotating auger to measure and dispense the powder into the bottles.

Feature

- Stainless Steel Grade 304 and Synthetic Material contact parts: conforming to the GMP suitable for food, pharmaceutical or chemical applications,
- PLC touch screen and interface: Filling is volumetric and is precise provided the product is consistent, The Volume can be set up relative to the weight of the product.
- Convenient and easy to operate. Servo motor-driven: giving a high precision, high torque and adjustable rotational (dispersion) speed. Standard machine is 380 Volt 50 Hz.
- Can also be supplied as a fully Automatic Volumetric Filling Line
- Easy cleaning

Specification:

Specification	DH-L1-S	DH-L1-M
Speed	15-40 / min	15-40 / min
Hopper	25L	50L
Dimensions	1180×720×1986mm	1780x910x2142mm
Air Supply	0.05cbm/min, 0.6Mpa	0.05cbm/min, 0.6Mpa
Weight	160kg	300kg
Power Supply	3~ + N + PE 415v 6A	3~ + N + PE 415v 6A
Filling Accuracy	100-500g ≤±1%	≥ 500g, ≤±0.5%
Filling Accuracy	10-100g ≤±2%	100-500g, ≤±1%
Filling Accuracy	1-10g ≤±3-5%	≤ 100g, ≤±2%
Weight	1-500g	10-5000g
Type	Auger	Auger & Weighing