

Automatic powder packaging machine CB-320P



The 250g 500g 1kg Automatic powder spice packaging machine good price can pack powdered products, such as flour, milk powder, corn starch, soy flour, glucose powder, ice cream powder, pepper powder, fish food powder, curry powder, cocoa powder, coffee powder, bean powder, washing powder, alkaline powder, organic fertilizer, etc.

Features:

- Full Chinese (or English) touch screen (the text can be set according to customer requirements).
- Siemens touch screen clearly shows all kinds of work status, operation instructions, easy to operate intuitive,
- Siemens PLC provide a stable working procedures,
- It can be preset 10 product formulations, to adapt to the rapid replacement of product packaging,
- Using intelligent thermostat, temperature can be controlled within 2 degrees

- Non-stop can be adjusted directly on the touch screen sealing position, correction and so on.
- With the die-tooth-type seal, packing more solid, but also the choice of straight lines, twill, anilox, etc.
- It can be used CE installation standards, electrical protection standards up to IP65,
- The packaging machine can be made of many kinds of bags, such as: flat bag (back seal, triangle seal, four side seal), three-dimensional bag (socket self-standing bag, triangle bag), bag, punching bag.
- All kinds of punched shapes can be designed by us for you.
- In order to highlight your bags of water chestnut clear, we have a special dedicated crimping device, your product gas release; we have a one-way valve on each of you.
- Overweight products will affect the packaging effect, we have a care device, it will hold a heavy product, to be packaged after the product shipped out.
- Product is too fluffy, the package is too small, there is a shock device can solve the problem for you.
- If your packaging film is a single layer of PE material, but also optional special PE membrane sealing device.

Technical Parameters:

Туре	CB-320P	CB-420P	CB-520P	CB-720P
Bag length	40-230mm(L)	80-300mm(L)	80-400mm(L)	100-480mm (L)
Bag width	20-150mm(W)	50-200mm(W)	150-250mm(W)	180-320mm (W)
Max width of roll film	320mm	420mm	520mm	680mm
Packing speed	5-60bags/min	5-60bags/min	5-60bags/min	5-50bags/min
Measuring range	1-500ml	150-1200ml	3000ml(Max)	6000ml(Max)
Air consumption	0.65Mpa	0.65Mpa	0.65Mpa	0.65Mpa
Gas consumption	0.3m³/minhan	gbo.em.antiwab	a . C O0₁4m³/min	0.4m³/min
Power voltage	220V/380V 50/60HZ	220V/380V 50/60HZ	220V/380V 50/60HZ	220V/380V 50/60HZ
Power	2.2KW	2.2Kw	4Kw	5Kw
Dimension(L*W*H)	820*1116*1395mm	1320*950*1360mm	1150*1795*1650mm	1780*1350*1950mm
Gross weight	450KGS	550KGS	600KGS	700KGS
Packaging style	Box bags,self-standing bags,punching self-standing bags,punching back bags,back sealing bags.			
Packing film	Paper/PE,PE/AL,Polyester/polyethylene, polypropylene,etc			