



Home Tabletop Vacuum Machine DZ-260/300/400



A home table vacuum machine is your ideal choice of entering the field of vacuum packaging because it's small, quiet, durable and competitively-priced.

Features:

Smart Digital Control Panel

- Quick multi programs switch
- Panel mask Support customization
- Support manual sealing
- Accurate parameter control

Food-Grade Main Structure

- Constructed of high-quality SUS304 stainless steel
- Use Switzerland laser cutting device to produce
- Smooth feeling by meticulous surface treatment
- Strong structure by finite element analysis
- Glossy chamber and beautiful brushed shell

Efficient Heat Dissipation

- Powerful thermal fan
- As soon as turn off machine, fan will close
- Patent design for thermal holes
- Available eight consecutive hours working

All Transparent Visual Lid

- Made of high-impact acrylic material
- Effortless designed hinges
- Durable sealing lid gasket by Special “V” sharped desig

Robust Sealing System

- Design patent for fastener of seal wire for add service life
- Double-seam is alternative
- Double-seam with cutting-off is alternative
- Two sealing bars is alternative
- Plug-in without cables sealing system is alternative

Easily Maintaining Design

- Simple to open or close the shell
- Clear oil level viewing window
- Not difficult to replace the oil of vacuum pump
- Easy to displace wearing parts

Technical Details

Model	DZ-260 O	DZ-260 PD	DZ-300 PJ	DZ-400 N
Vacuum Pump Capacity	10m3/h	10m3/h	10m3/h	10m3/h
Seal Length S	260mm	260mm	300mm	400mm
Distance Between Seal bar B	350mm	350mm	335mm	335mm
Chamber Depth D / D*1	80/120mm	50/90mm	135/185mm	50/100mm
Chamber Size	280×385mm	280×385mm	320×370mm	420×370mm
Chamber Shape	Arch*2	Flat	Flat	Flat
Power	0.37kW	0.37kW	0.37kW	0.37kW
Connection*3	230V/50Hz	230V/50Hz	230V/50Hz	230V/50Hz
Net Weight / Gross Weight	35/43kg	33/39kg	39/45kg	43/52kg
Dimensions W x L x H (mm)	480×330×400	480×330×375	480×370×450	480×470×385
Shipping Dimensions (mm)	560×410×435	560×410×410	560×420×490	540×530×435
Circle Time	1-2/min	1-2/min	1-2/min	1-2/min