

KD-450 Extended Exhaust High Speed Automatic Pillow Packing Machine



It is suitable for packing medical mask, hotel wet towel, towel, paper towel, dried noodles, ham sausage, instant noodles and other long irregular bulk materials.

Features

Compact structure, stable performance, simple operation. The third generation of three servo control, bag length is set and cut, no need to adjust the empty walk, film color tracking step in place, save time and film. Using imported electrical appliances, touch man-machine interface, parameter setting is convenient and fast. Fault self diagnosis function, fault at a glance. High sensitivity photoelectric eye color mark tracking makes the sealing and cutting position more accurate. Temperature independent PID control, better suitable for all kinds of coating materials. Positioning stop function, no sticking knife, no film. Simple rotation system, more reliable work, more convenient maintenance. All the control is realized by software, which is convenient for function adjustment and technology upgrade.

Technical Parameters

Equipment model	Kd-450 full automatic pillow packing machine
Use packaging materials and specifications.	Suitable for all kinds of OPP heat sealing film, composite film, coated paper, aluminum foil film and aluminum plastic composite film
Model specification	4600*850*1500
Packaging speed	20-150 bags / min
Maximum finished bag making specifications	Length.330mm. width.180mm. 'height.80mm
Minimum material specification	Long. 150 mm, W, 50mm high, 5mm
Rated voltage v. power	AC220v.2.7KW
Compressed air pressure	0.5-0.7 (Mpa)
Compressed air consumption	> 0.36 (m ³ /h)
Noise (DB)	Low noise. 60-70db
Machine weight kg	550Kg
Motor frequency regulation capability	0-50Hz
Automatic control ability of production process	Automatic coding