

## ***WP-BF series Single Station Premade Bag Packing Machine***



### **Application**

- ◎ Applicable Bag Types: four side seal bag, standup pouch bag, zipper bag(option) and so on.
- ◎ Applicable Bag Material: multi-layers laminated films, for example: PET/PE. Film thickness 0.05-0.15mm.
- ◎ Applicable Products: a variety of snack food, candy, bean, pet food, dried fruits, sugar, milk powder, coffee powder, etc.

### **Feature**

- ◎ PLC control, man-machine interface, easy to operate and maintain.
- ◎ With cushion structure, stable movement with lower noise.
- ◎ Equipped with safety devices, abnormal air pressure shutdown, heat and disconnection alarm etc..
- ◎ Complete detecting function, no bag opening no products filling, no products filling no bag sealing.
- ◎ The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

### **Technical Parameters**

Model	WP-BF1300
Station Number	one station
Bag size (mm)	L*W=(100~350)*(80~300)
Packing speed	0~15 ( bags/min)
Voltage	1.2KW/220V/50(60)Hz
Gas Pressure	0.4~0.8MPa
Gas Consumption	0.3m³/min
Machine Size (mm)	1750*510*1350
Machine Weight	200Kg