



FL7030+BSE-6040A Shrink Wrapping Machine For Carton Box



Products Description

Shrink Wrapping Machine For Carton Box

1. The film sealing cutting machine is feature on the unique optimized design of linear feeding
2. The machine introduce foreign advanced technology and production technology, and the equipment performance is stable and reliable
3. The PLC, which is programmable logic control is used to realize the integration of machine, electricity and pneumatic.
4. Linear feeding and the length of the package is not limited.
5. Compared with ordinary side feeding machines, this machine has the advantages of speed and connection.
6. Specially designed sealing blade ensure a firm sealing line. no cracking and no sticking
7. Imported photoelectric detection makes accurate position.
8. Imported durable conveyor belt increase the transmission speed of the inverter control belt.
9. User-friendly control box for easy operation.
10. Three sets of horizontal photoelectric detection can deal with different products
11. The back end of the sealing and cutting machine is equipped with a pressing device, and no displacement occurs for items with light weight.
12. According to the packaging requirements of the product a vertical double sealing system can be installed to make a fully enclosed

PE heat shrink machine

1. BSE-6040A Shrink Wrapping Machine For Carton Box adopts imported double-wind motor to make the hot air in the furnace evenly distributed. and the effect after shrinking is more beautiful.
2. The adjustable hot air circulation structure in the furnace chamber makes the equipment more energy efficient
3. The solid steel rod is used to outsource the imported silicone tube. and the chain-type conveying silicone is durable
4. The whole Shrink Wrapping Machine For Carton Box adopts Taiwan Delta inverter to control the transmission speed. and stepless speed regulation is available

Technical parameter

Model	FL7030
Voltage	110,220,380V
Power	2kw
Max sealing size	700*300mm
Air source	6kg/cm ³
Work table height	850±50mm
Sealing temp	0-200°C
Packing speed	8-22
Machine weight	465kg
Machine size	1650*920*1895mm

Model	BSE-6040A
Voltage	220V 380V
Power	28kw
Convey speed	0-10m/min
Shrink tunnel	1800*600*400mm
Loading	30kg max
Shrink film	PE POF PVC
Machine weight	470kg
Machine size	2800*850*1760mm