



ST-12030AF/SM-13040 Dual Side Sealing Packing Machine



Dual Side Sealing Packing Equipment adopt international advanced technology manufacturing, and imported parts, electrical components and pneumatic components with two positions where the membrane can be heated down, so that you can add membrane at any time, be sure the machine keeps running always.

Dual Side Sealing Packing Machine Service body and part performance precision and durable, operation process and no vibration, operation stability, long life span, high efficiency. Meanwhile, the Sealing Packing Machine with Shrink Tunnel equipped with blade protection device, avoid operation when he accidentally stabbed. It also can be used separately, or contact with the production line together.

Technical Parameters

Model	ST-12030AF	SM-13040
Machine Dimensions (mm)	L2700 X W1840 X H1985	L2800 X W1680 X H1690
Tunnel Chamber Size (mm)	/	1800 X 800 X 400
Max Packing Size (mm)	L Unlimited, W+H≤1100 H<300	1500 X 1100 X 300
Sealing Blade Size (mm)	L 1000	/
Power Source	3PH 380V 50Hz	
Power (kw)	3	40
N. W. (kg)	1200	1100
Temperature Range (℃)	0-300	0-300
Capacity	3-12 pcs/min	20-30 m/min
Air Source (kg/cm ²)	6.0-8.0	/
Applicable Film	POF/PE	POF/PE