# *ASM-501 Shrink Tunnel*



Shrink tunnel can be used with Impulse Foot Sealer. Refer to our Overwrapping Machine for larger number of packaging.

This Shrink packing machine can be used with a when it is packaged in a small amount. Please refer to our for a large number of packaging.

**Features**

►Automatic temperature control.
►Continuous operation of roller converyor, speed adjustable.
►Moisture proof capability can prevent products from dust moisture and thief.
►Run with PVC, POF, PP shrink material.

**Options**

Sealing machine PH-300/450, packing steps: Put products into shrinkable bags → sealing (sealing machine PH-300/450) → put into shrink tunnel (ASM-501A/B/C).

**Applications**

Suitable for outer packing for stationery, books hardwares, tools, toys, cosmetics, gift boxes, woodworks, foods etc to prevent products from dust, moisture and thief.

## Specification

| MODEL / SPECIFICATION | ASM-501A | ASM-501B | ASM-501C |
|---|---|---|---|
| **Conveyor Speed (m/min)** | 0 - 6 | 0 - 6 | 0 - 6 |
| **Max. Temperature** | 180°C | 180°C | 180°C |
| **Tunnel Size (L x W x H mm)** | 1200 x 400 x 200 | 1200 x 500 x 250 | 1200 x 500 x 400 |
| **Motor** | 60W x 2, 25W x 1 | 60W x 3 | 60W x 3 |
| **Heater** | 7.65 KW | 10.2 KW | 10.2 KW |
| **Material** | PVC / POF / PP | PVC / POF / PP | PVC / POF / PP |
| **Machine Size (L x W x H mm)** | 1750 x 680 x 1150 | 1750 x 780 x 1200 | 1750 x 780 x 1350 |
| **Case Size (L x W x H mm)** | 1920 x 760 x 940 | 1920 x 860 x 1050 | 1920 x 860 x 1250 |
| **N.W. (kgs) / G.W. (kgs)** | 120 / 200 | 150 / 250 | 200 / 300 |