

3139/38-N Printer Applicator



The Label-Aire® Model 3139/38-N Printer Applicator makes print and apply labeling even easier.

The Model 3139/38-N Printer Applicator thermal transfer or direct transfer imprints and applies labels around any corner or two labels on adjacent panels utilizing a vacuum zed drum. The Model 3138-N with its built-in label unwinds and rewind capabilities is utilized for one-to-one print and apply allowing for the immediate application of each label as it is printed. The 3139/38-N's sturdy swing arm can be configured for cartons or pallets. The heavy duty square-frame mounting stand can be bolted to the floor for added stability. The 3139/38-N is compatible with most O.E.M. printers.

Put this advanced workhorse printer applicator to work for you. The Model 3139/38-N Printer Applicator is designed to run seamlessly in your operation, saving you money in the long run.

Specs

- **Dimensions:**
Height: 62.29" (1.58 m),
Width: 24" (.61 m) Min. (Max. width dependent upon arm length.),
Length: 56.91" (1.45 m)
- **Weight:** 500 lbs. (227 kg)
- **Standard Label Dimensions:**
Label Width: Up to 7" (177.8 mm),
Label Length: Up to 24" (610 mm) (printer dependent)
- **Dispense Speed:** Up to 16" (406 mm) per second depending on printer and label size
- **Label Placement Accuracy:** Up to +/- 1/8" (3.175 mm)
- **Electrical:**
115 Volts AC 60 Hz 5 Amps.,
220 Volts AC 50 Hz
- **Air (as needed):** 4 cfm at 90 psi for most applications
- **Options:**
Compatible with most O.E.M. print engines,
Wide range of arm lengths,
RFID configurable