

HESLY

Packaging Line DZ-120P and BT-2000L



This machine is suitable for bottle (round, square bottle), into carton automatically. On line product feeding and detecting, carton opening and forming, products and leaflet push into carton, printing batch number, sealing carton with tuck-in or hot melt glue device. Automatically reject lacking of leaflet or product and finished product out.

Features:

1. International famous brand of electrical component such as PLC touch screen, frequency inverter, etc.
2. Adopt human-machine operation system.
3. Automatically stop when machine is overload.
4. Automatically reject lacking of package product and leaflet.
5. Automatically display trouble, Alarm and count finished products.
6. Stable performance, operation is easy.

Main Technical Parameters:

Item	Parameters	
Encasing speed	30-120 boxes /min	
Box	Quality requirement	250-350g/m ² [Base on carton size]
	Dimension range (L×W×H)	(65-160)mm×(30-85)mm×(15-50)mm
leaflet	Unfold leaflet specification	(80-230)×(90-170)mm
	Fold range	(1-4) fold
Compressed air	Working pressure	≥0.6mpa
	Air consumption	120-160L/min
Power supply	380v 50HZ	
Main motor power	0.75kw	
Machine dimension(L×W×H)	3400mm×1200mm×1800mm	
Machine weight	1200kg	

BT-2000L Model Overwrapper Machine:

SIZE RANGE (IN MM)	MIN. STANDARD	MAX. STANDARD
Length (L)	40	200
Width (W)	30	140
Height (H)	10	80
Maximum output *	40-80strokes per minute	
Film width	60-260MM	
Voltage	220V 50HZ ,ONE PHASE	
Power	4KW	
N.weight	900Kg	
Film-roll diameter max.	320 mm	
Packaging material	Polypropylene,Bopp	
Basic configuration	HOPPER INFEED	
OVERWRALL DIMENSION	2600X960X1600MM	
Optional accessories	PLC controller ,touch screen, printmark registration, Date printer, safety cover, conveyor belt.	
* depending on product, machine configuration and packaging material		