

High Accuracy Rotary Packaging Machine XY8-250-K



This device consists of a rotary pouch packing machine, intelligent combination weighing machine, the bucket elevator, working platform supporting made.

Mainly applicable to a variety of solid, granular, massive and materials weighed. Such as puffed food, snack foods, nuts, seeds, almonds, pistachios, pine nuts, candy, jelly, beans, food, frozen food, pet food, all kinds, hardware materials and other materials like automatic feeding, automatic take bag, playing yards, open bags, quantitative filling, pumping nitrogen sealing, product delivery.

The rotary pouch packing machine main features:

1. An easy to operate, with Germany's Siemens PLC control with touch screen control system, easy to operate.
2. Frequency control, frequency control devices used with this unit, within the provisions of the speed can be adjusted.
3. Automatic detection function, if not open the bag or open bags incomplete, no feeding, no sealing, the bag can be used again, do not waste materials, saving production costs.
4. Safety device, when the working pressure is not normal or heating pipe failure, it will alarm.
5. Quick-change bag size, robotic device width can be adjusted quickly and easily.
6. Random with plexiglass security door, when the door is opened the machine immediately stops running play a protective role of the operator.
7. Adopts imported plastic bearings, without refueling, reduce the material contamination;
8. Oil-free vacuum pump, to avoid contamination of the production environment.
9. Packing materials loss low, what this machine is preformed bag, packaging bag pattern perfect sealing quality, resulting in improved product quality.
10. Meet the food processing industry hygiene standards, machines and materials or bags made of stainless steel parts in contact with food hygiene requirements or other material processing, to ensure food hygiene and safety.
11. Wide range of packaging, by selecting the different measurement devices, can be applied in a liquid, paste, granule, powder, irregular lumps and other packaging materials.

Specifications:

Model No.	XY8-250-K
Bag Type	Flat bag, 3 sides sealing, 4 sides sealing, Zipper bag, Doypack etc.
Packing Bag Material	Composite film, PP etc.
Bag Size	W:100-250mm L:150-300mm
Weight Range	30-2500g
Packing Speed	30-60 bags/min(speed is decided by material and its filling weight)
Packing Accuracy	$\leq \pm 1\%$
Voltage	3.95KW,AC380V,50HZ
Machine Dimension	4340X2000X3700mm