

L Type Automatic Heat Hot Shrink Packing Machine FQL-450



Performance characteristics

1. Fully enclosed packaging.
2. Automatic film feeding, bag making, sealing and cutting, waste collection, leveling, shrinkage and packaging finished products are completed at one time.
3. Constant temperature type super-grade aluminum alloy sealing cutter, anti-sticking, fine sealing line, no coking, no smoking, zero pollution.
4. Cutter packing material will automatically rebound after.
5. The size of the package can be adjusted arbitrarily without changing the mould.
6. All conveyor belts are covered with PTFE heat insulating pipes, without ironing hands or damaging membranes.
7. The contraction chamber adopts double-cycle hot air system, and the temperature can be adjusted arbitrarily.
8. Conveyor motor adopts CVT motor, which has long service life and low noise.

Scope of application

Suitable for large quantities in software, food, cosmetics, printing, pharmacy, floor, ceramics, beverage, hardware and other industries. Heat shrinkable packaging.

Main technical parameters

Model	FQL-450 Sealing and cutting machine
Power Supply	220V/50HZ
Power	1.35KW
Highest speed	0-15m / min.
Packing height	≤150mm
Packing width	≤350mm
Package size	Width + Height ≤400mm
	Length + Height ≤ 480mm
Applicable film	POF folded film, PE membrane
Platform height	780-850mm
Air pressure	4KG/M ²
Main material	Carbon steel
Weight	300KG