

Automatic Single Head Ropp Cap Sealing Machine PARCS-60



Automatic ROPP Cap Sealing Machine is versatile, self-supported on stainless steel leg with height adjustable adjustment system. This ROPP Capping Machine is precision built on sturdy welded MS frame completely enclose in stainless steel sheet and doors are providing to facilitate the servicing of machine.

Operation:

The feed container moving on conveyor belt are fed into an infeed star wheel through In-feed worm, star wheel bringing the container below the sealing head in the subsequent indexing part, meanwhile the bottle pick up a cap from the delivery chute of cap filling bowl, where the body and the neck of the container are positioned below the rotating head, where the sealing head is performing perfect operation of threading & sealing.

Technical Specification:

Model		PARCS-60
Output/Hour*		2000 to 3600 bottles
Direction of Movement		Left to Right
No. of Sealing Head		1 Nos.
Electrical Specification**	Main Motor	1.5 HP / 415 Volts / 50 Hz.
	Cap Feeding Bowl	0.25 HP / 415 Volts / 50 Hz.
Height of Conveyor**		860 mm to 910 mm
Machine Dimensions**		1500 mm (L) x 700 mm (W) x 2000 (H) Approx
Case Dimensions		1700 mm (L) x 900 mm (W) x 2200 (H) Approx
Net Weight		300 Kgs. Approx.
Gross Weight		500 Kgs. Approx.
Change parts required		(A) Container: Star Wheel, Center guide, Feed Worm
		(B) Cap: Die, Delivery Chute, Bowl