

Automatic Shrink Wrap Machines L Bar Sealers WE-400LA



Automatic L Sealer Shrink Wrap Machines are widely used in the assembly line of mass production and packaging. It uses an electronic eye to detect products when they pass through the conveyor. After a product passes the sealing arm, the seals fully enclose the product in shrink film. After the seal, products continue to pass into the shrink tunnel. The shrink tunnel has recirculating heat to shrink the film to the product evenly. Fully wrapped products exit the tunnel, and the film is conformed tightly to the product.

Parameter:

Model	WE-400LA
Sealing type	L-sealing (L-bar)
Power supply	380V/50-60Hz/3Phase
Speed	15-35 packs per minute(depends on product size)
Product size	width+height≤400mm length+height≤480mm
Filling volume	Sealing height≤125 mm Packing width≤350mm
Film	center-folded polyolefin(POF)film
Max film size	530mm(width)x280mm(outer diameter)
Power	1.5KW
Air compressor	≤0.5MPa(5bar)
Gross Weight	300kg
Working height	780-850mm
Sealing system	Special durable alloyed sealing knife with anti-stick Teflon coats
Machine material	Carbon steel

	WE-450C
Power supply	380V/50-60Hz/3phase
Oven size	1200mm(L),entrance 400(W)*220(H)mm
Conveyor	Conveyor chains with rotating silicon coated rods, speed variable
Power	7KW
Working height	780-850mm
Gross Weight	160kg
Machine material	Carbon steel