

## *WP-TY-series Tomato Ketchup Pouch Packing Machine*



The tomato ketchup pouch packing machine suitable for packing catsup, thick paste material in the medicine, food, daily chemical and other industry.

### **Product feature and application**

- It integrates metering, bag-making, packaging, sealing, printing and counting.
- Standard positioning with servo film transporting system; stable for transporting film with two synchronous belts;
- High automation with auto correction function.
- Reasonable structure, convenient adjusting operation and maintenance.
- It is equipped with advanced level switch and static eliminator

**Main technological parameter:**

Bag shape	packing material	volume	Electricity	compressed air	capacity	
WP-TY-400	34/-SIDE	L:30-120	2-30ML	220V/380V	240kgs	30-55bags/min(single-lane)
		W:40-65		50/60HZ	0.8*0.76*1.7m	under 120bags/min(multi-lane)
				2.0Kw		
WP-TY-380	3/4-side sealing	L:55-110 W:30-80	40ML	220V,50Hz,1.5Kw	320kgs	80-100bag/min
					0.7X0.85X1.8m	
WP-TY-360	pillow sealing	L:50-170	100ML	220V,50Hz,1.5Kw	350kgs	50-90bag/min
		W: 30-130			1.0 X 0.9 X 1.9m	
WP-TY-340	pillow sealing	L50-300	1000ML	220V,50Hz,1.8Kw	400kgs	35-50bag/min
		W:30-200			1.1X1.0X2.1m	
WP-TY-320	pillow seaaling, gusset stand bag, punched bag	L:50-300	1200ML	220V,50Hz,2.5Kw	500kgs	30-60bags/min
		W:60-200			1.4X1.1X1.7m	
WP-TY-300	pillow seaaling, gusset stand bag, punched bag	L:80-400	3000ML	220V,50Hz,4Kw	750kgs	30-60bags/min
		W:50-250			1.45X1.3X1.75m	
WP-TY-280	pillow seaaling, gusset stand bag, punched bag	L:80-500	5000ML	220V,50Hz,5Kw	950kgs	30-60bags/min
		W:80-350			1.7X1.5X2.0m	