

Automatic Doypack Zipper Pouch Wheat Flour Packing Machine JYT-160C/210C/260C/320C



It is suitable for powder: milk powder, coffee powder, food additives, condiments, tapioca powder, coconut powder, pesticide powder, fertilizer granules etc.

All type of heat sealable preformed side seal bags, fin seal bags, gusseted bags, block bottom bags, zip-lock reclose able bags, stand-up pouch with or without spout ect.

Product advantages

1. The metering and packaging system consists of a horizontal bag-feeding packaging machine and a blanking system.

2. It is convenient and simple to put the bag in the bag slot, and it is equipped with an automatic bag pressing device.

3. Equipped with imported pressure sensing device to achieve the effect of no cutting and no sealing, saving packaging bags.

4. Adopt color touch screen, simple operation and multi-functional design.

5. The machine adopts the appearance of stainless 304L, and the carbon steel frame part and some accessories are processed with acid-resistant and salt-resistant anti-corrosion treatment layer.

6. Material selection requirements: Most of the accessories are produced by moulding, and the main materials are 304 stainless and alumina.

7. Various coding device, exhaust and punching systems can be selected.

Product Specification

Model	JYT-160C	JYT-210C	JYT-260C	JYT-320C
Filling range	5~300ml	50-1000ML	200-2000ML	500-3000ML
Packaging speed	20-60 bags/min	20-60 bags/min	10-60 bags/min	10-50 bags/min
Bag length	100~210mm	110*330mm	150*400mm	150*500mm
Bag width	80~160mm	90*210mm	150*260mm	200*320mm
Machine size	1700*1050*1100mm	2150*1350*1300mm	2450*1200*1200mm	2800*1200*1200mm
Air consumption	0.35m ^a	0.5m³	0.7m³	0.7m²
Applicable bag type	Three-side seal, four-side seal, back seal, Stand-up bag, M-shaped bag, special-shaped bag	Three-side seal, four-side seal, back seal, Stand-up bag, M-shaped bag, special-shaped bag	Three-side seal, four-side seal, back seal, Stand-up bag, M-shaped bag, special- shaped bag	Three-side seal, four side seal, back seal, Stand-up bag, M- shaped bag, special shaped bag
Machine weight	600kg	900kg	1100kg	1500kg
Machine power	220/380V.50H Z, 2.5KW	220/380V,50HZ,3.5KW	220/380V,50HZ,3.5KW	220/380V.50Hz 3.5K