

## ***KD-450D Automatic Pillow-shaped Packaging Machine (Downward film type)***



Using original single servo or double servo motor control, compared with other domestic and foreign similar inverter motor or inverter control products, more intelligent, higher packaging precision, wider adjustable range, more accurate control, lower scrap rate and better stability. Due to the full open box structure, the transmission structure is clear at a glance, and the maintenance is more convenient;

### **Features**

Compact structure, stable performance and simple operation. Double frequency control, the bag length is set and cut, no need to adjust the empty walk, one step in place, save time and film. Using imported electrical appliances, touch man-machine interface, convenient parameter setting, fault self diagnosis function, fault display at a glance. High sensitivity photoelectric eye color mark tracking makes the sealing and cutting position more accurate. Temperature independent PID control, better suitable for all kinds of coating materials. Positioning stop function, no sticking knife, no film. Simple rotation system, more reliable work, more convenient maintenance. All the control is realized by software, which is convenient for function adjustment and technology upgrade.

## Technical Parameters

Maximum film width	450mm
Maximum packaging capacity (depending on material)	50-180 times / minute
Suitable for film thickness	0.03-0.06mm
Bag length	65-330mm
Package width	25-200mm
Packing height	5-70mm
Total power	2.7Kw220V
Machine dimensions (L x W x H)	4200 x1050x1500mm
Total weight	750kg