

Multi head CombinationWeigher

The machine is best for...

Extruded snacks like Kurkure & Potato Chips, Farsan, Chiwda, Namkeen, Dry Fruits, Pulses, Grains, Tea, Sugar, Seeds, Frozen cut vegetable etc.

High Speed & High Precision weighing is the uniqueness of multihead weigh filler. KAWACH series is well for its pouch finish & sealing intactness which prevents leakage of inert gas from pouches & gives extended product shelf life.

Additional Systems

Online batch coding device

Inert gas flushing system

3 side, 4 side, center sealing, guzzeting, block bottom etc. (optional)

Batch cutting device

'No material machine stop

Static charge eliminator for dust free sealing

Available in GMP model for pharmaceutical users

'D' cut or Euro slot or any shape which made to carry the bags easily



Multi head Combination Weigher

Filling Capacity (Range)	5 g to 5 kg
Output Speed	20 to 60 pouches / min (depend on model)
	depend on product flow ability and bulk density)
Packaging Material	Laminated films
Heating System	Hot bar induction, controlled through PID
Control	PLC controlled
Mode of Operation	Pneumatic
Reel Core Diameter	70 to 76 mm
Roll Holding	Pneumatic shaft
Maximum Roll Weight	50 kg
Electricity Required	420V, 3Ph, 50Hz
Compressed Air Required	8 CFM at 6 bar Pressure
Machines Weight	1400 kg (approx)
Machines Dimension	1800 (W) X 1800 (L) X 3350 (H) mm
Weighing Head Option	8 H, 10 H, 14 H
Available In Variety	5 gm -100 gm, 20 gm - 200 gm, 5 - 200 gm,
Of Models	100 gm to 500 gm, 200 gm - 1 kg, 500 gm - 2 kg, 1kg - 5 kg

Note: The design / specification are subject to change without notice on account of continuos improvement in product quality.

Special Features

- PLC controlled machine with touch screen.
- Built in self fault diagnosis system.
- Password protection for settings.
- Minimum maintenance.
- If 'No material machine stop.
- Batch cutting device (Optional)
- Epoxy powder coated structure.
- High filling accuracy.
- Weight adjustment through touch screen.
- Motorized film trolley alignment systems.
- High density heaters for long life & minimum warm up time.
- PID temperature controlled for precise temperature controllers.



Flexipack Systems Pvt. Ltd.

Manufacturer of Flexible Packaging Machinery & Allied Systems

Regd. Office & Factory: Plot No. 6 & 17, Gat No. 1556 / 1559, Dehu - Alandi Road, Shelarwasti, Chikhali, Tal. Haveli, Pune - 412 114 Ph.: +91-20-27492722; 66346900, Fax.: 66346904. Email: saurabhpackaging@hotmail.com; sales@saurabhflexipack.com website: www.saurabhflexipack.com

Branches: Mumbai, Ahmedabad, Rajasthan, Chenni, Hyderabad, Bangalore, Kolkata, Delhi

