



## Semi Automatic Auger Filler | VTOPS-P6



Semi automatic auger filler of model VTOPS-P6 was released in June 2019 on the exhibition of Propak China 2019. Mainly used for fill both free flowing and non-free flowing products.

The P6 series auger filler are equipped with the touch screen, PLC and servo system produced by Delta. And equipped with monitor able and easy clean hopper.

### Technical Parameters:

- Model: VTOPS-P6
- Metering Range: 5 grams to 5000 grams  
*Need to replace the Auger Filler and Tube to guaranteed accuracy and speed; details reference the "Some Problems You Will Meet When Picking an Auger Filler [2]" please!*
- Fill Speed: 0-70 fills / minute
- Filled Error:  $\leq \pm 1\%$
- Contact Materials: SUS 304
- HMI: LCD Touch Screen
- Control System: PLC
- Monitorable Hopper: Yes [2]
- Easy Clean Hopper: Yes [3]
- Filling Motor: Servo Motor [4]
- Fill Control: Timer based / Sensor based
- Container: Bottle, jar, pouch, can
- Hopper Volume: 50 liters
- Power: Single-phase AC 220V 50Hz 1.5Kw
- Machine Dimensions: 800× 800×1960mm
- Machine Weight: 200 Kg