

Cosmetic Filling Machine High Productivity For Aluminum Tube



Aluminum tube filling machine is used to fill and seal the plastic tubes and plastic-aluminum laminated tubes. It is widely used in the cosmetics, medicines, lubricants, adhesive and shoe polish, pigments and food sauces etc.

Description:

Aluminum tube filling and sealing machine used for Aluminum Tube is one of main latest products of our company. It is full automatic. This machine can be used for filling cream and liquid materials, and it is characteristics with firm filling, high precision of dosage. The three functions of filling, sealing and batch numbering can be automatically completed. It is widely used in pharmacy, daily chemical, food, chemical industries, such as for filling pharmacy cream, hair color ante, toothpaste, leather oil, glue, AB glue, Nanp-epoxy adhesive, Neoprene adhesive etc. Convenient and quick dosage adjustment, high efficiency, good-looking, compact structures are the features of the machine. The tube cups can be adjusted according to the tube dimensions. The important parts of the machine which contact directly to the filling material are made of stainless steel (SUS304 is for general use, and SUS316L is for pharmacy use). A special valve makes this machine be suitable for filling cream and liquid material. It is an ideal and economical filling machine in the pharmacy, daily chemical, fine chemical and other fields.

Structural features:

Filling speed and measurement accuracy to facilitate the adjustable, stable performance. Each turn a station, to complete the metal four-fold four-fold function. The use of automatic folding cam, safe airtight, to ensure product quality. This machine adopts stepless speed regulation. For different diameter of the metal pipe, as long as the mold can be put on a different diameter, the replacement is both convenient.

Technical Parameters:

主要技术参数 TECHNICAL PARAMETER

电源 Power supply	220V、50Hz
生产能力 Capacity	10~30支/分 10~30 pcs/min
灌装范围 Filling volume	20~150ml
软管直径 Aluminum tube diameter	Φ13~Φ32mm
电机功率 Motor power	1.5kw
工位数 Working positions	16
重量 Weight	250kg
外形尺寸 Dimension(L × W × H)	1700 × 1000 × 1700mm