

*Linear Weighing System Packaging Machine **BM-L***



BM PACK-L PACKAGING MACHINE WITH LINEAR WEIGHER

*Suitable for granule type of products. The target weight is controlled by linear vibration units. With respect to product type and desired speed; 2 or 4 line types are available. The magnitude of vibration level for each line is adjustable. The accuracy of each filling is controlled by tuning each line vibration magnitude. The average accuracy is depend on product type.

*All surfaces touching to products are AISI 304 stainless steel.

*Easy dismountable collar set design.

*Package length should be controlled by print mark or feeding duration.

*Printer state is checked continiously.

*Wrapping material is driven by AC motors.

*Pneumatic driven horizontal sealing and cutting.

*Impulse or heat sealing units for different type of wrapping materials.

*Suitable for CE standarts.

*7 inch touch screen wtih several languages.

Optional Fittings and Equipments

*Gas flushing system.

*Bucket conveyor for product feeding

*Finished prouct conveyor

*Special Vacum supported belts. (Increases belt life time and machine speed)

*Euro-Slot tool.

*Barcode and date printer.

Contact us for different type of packages, products and capacities.

Technical Data:

Width	1700mm
Length	2000mm
Height	3220
Weight	500kg
Speed (Package/Minute)	
Package Length	max:400mm
Package Width	max:200mm
Film Bobbin Diameter	max:320mm
Film Bobbin Width	max:480mm
Power Consumption	5.5 Kw
Working Voltage	380V 3 Phase 50Hz
Air Consumption	150 lt/Minute
Air Pressure (min.)	6 Bar

