



## ***BM-A Series Packaging Machine with Auger Filler***



- The machine is designed for powder and similar fine products. The target weight of each filling is
- Controlled with fast and accurate servo driven specific auger (worm screw).
- The auger type and diameter changes with respect to product type and target weight.
- All surfaces touching to products are AISI 304 stainless steel.
- Easy dismountable collar set design.
- Package length should be controlled by print mark or feeding duration.
- Printer state is checked continuously.
- Wrapping material is driven by AC motors.
- Pneumatic driven horizontal sealing and cutting.
- Impulse or heat sealing units for different type of wrapping materials.
- Suitable for CE standards.

### **Product Description:**

<b>Bag Size:</b>	(Length):80-400(mm) (Width):150-250(mm)	<b>Packing Speed:</b>	5-60(bags)/(min)
<b>Max Film Width:</b>	520(mm)	<b>Film Thickness:</b>	0.04-0.09(mm)
<b>Pulling Film Type:</b>	Dual Belt Tension Membrane	<b>Air Consumption:</b>	0.8Mpa 0.4m/min
<b>Power Source:</b>	2.2kw 220v 50Hz	<b>Measuring Range:</b>	Max5000ml
<b>Dimension:</b>	(L)1500*(W)1140*(H)1540mm	<b>Weight:</b>	550kg