

FFB-S Side Sealing Shrink Packing Machine



A new type of packing machine manufactured by Feifan, FFB-S is the equipment for shrink packing widely used in the area of dairy, chemical and daily articles. It is developed based on the side sealing packing machine. This model makes the sealing at the side of the packing product so that end sealing and longitudinal sealing shaped formation U. This kind of sealing doesn't effect the printed design on the film and also avoid the easy broken of vertical sealing, make the package be more beautiful.

Packing material: PVC POF and other material which we tested suitable for packing

Options: Date coding machine, film recovery system, auto feeding system, alcohol spray system, label sticker and so on.

Technical Parameters:

| Model | FFB-S5912 | FFB-S5915 | FFB-S6812 |
|----------------------------------|----------------|----------------|----------------|
| Max Film Width (mm) | 340 | 340 | 430 |
| Speed (Bag/min) | 30-130 | 30-130 | 30-130 |
| Length of pack (mm) | 70-450 | 70-450 | 70-450 |
| Pack Width (mm) | 10-150 | 10-150 | 10-200 |
| Pack Height (mm) | 5-65 | 5-85 | 5-65 |
| Electric Power Voltage (V) | 220 | 220 | 220 |
| Total Installed Power (Kw) | 4 | 4 | 4 |
| Power of electrical heating (Kw) | 15 | 15 | 15 |
| M a s s (K g) | 1200 | 1200 | 1300 |
| Dimensions (L×W×H)(mm) | 5700×1230×1800 | 5700×1230×1800 | 5700×1320×1800 |

| Model | FFB-S6815 | FFB-S7212 | FFB-S7215 |
|---|------------------|------------------|------------------|
| Max Film Width (mm) | 430 | 470 | 470 |
| Speed (Bag/min) | 30-130 | 30-130 | 30-130 |
| Length of pack (mm) | 70-450 | 70-450 | 70-450 |
| Pack Width (mm) | 10-200 | 10-220 | 10-220 |
| Pack Height (mm) | 5-85 | 5-65 | 5-85 |
| Electric Power Voltage (V) | 220 | 220 | 220 |
| Total Installed Power (Kw) | 4 | 4 | 4 |
| Power of electrical heating (Kw) | 15 | 15 | 15 |
| M a s s (K g) | 1300 | 1400 | 1400 |
| Dimensions (L×W×H)(mm) | 5700×1320×1800 | 5700×1360×1800 | 5700×1360×1800 |