

## *Fast Speed Flow Packaging Machine JY-600*



Suitable for packaging various kinds of regular objects like biscuits, pies, chocolates, bread, instant noodles moon-cakes, drugs, daily appliances, industrial parts, paper boxes, plates, etc

### **Feature:**

1. Photoelectric sensor is highly sensitive to tracking color target, The numerical input about the position of sealing and cutting make the position more accurate.
2. Maintenance-free barycenter type unloader.
3. Adjustment mechanism for material handing without stop.
4. Easy and fast adjustment of change over, the machine has strength extensibility, could fill two or even more products into one bag by added filling device.
5. Double frequency converter controller, length of package will cut immediately once setting, adjustment needless, saving time and film.
6. Touch screen, convenient adjustment.
7. Self-checking function, trouble can be read easily. High sensor photoelectric color chart tracking, make the cutting position more correctly.
8. Dependant temperature PID controlling suitable for various materials of packaging membrane. Position stop function, no adhesive and no waste of membrane. Clean rotation system, more reliable operation and more convenient maintenance.
9. All the controlling operates by the software, convenience for function adjustment and technical up grading.
10. Equipped with high-precision empty bag checking and rejecting device.
11. Equipped with steel character impressing at the intermediate sealing and continuous printing apparatus.
12. The terminal sealing cutter is always open at halt mode.
13. Smooth performance and low noise, perfect package appearance, Sensible safety device and no pollution during production to get Friendly working environment.

**Parameter:**

<b>Model</b>	<b>JY-450</b>	<b>JY-600</b>	<b>JY-700</b>
Film width	Max.450mm	Max.600mm	Max.700mm
Bag length	120-500mm	120-500mm	120-500mm
Bag width	50-180mm	100-280mm	100-330mm
Product's height	Max.80mm	Max.80mm	Max.80mm
Packing speed	30-150bags/min	20-150bags/min	20-150bags/min
Power	220V 50/60HZ 2.8KW	220V /60HZ 2.8KW	220V 50/60HZ 2.8KW
Machine dimension	4020x820x1450	4020x920x1460	4020x980x1480
Machine weight	650kg	680kg	720kg