



Zipper Bag Powder Auto Filling Sealing Packing Machine CB8-200PC



Specifications:

- Model CB8-200PC is Automatic stand up pouch filling sealing machine for powder.
- Its main usage is powdered products, such as flour, milk powder, corn starch, soy flour, glucose powder, ice cream powder, pepper powder, fish food powder, curry powder, cocoa powder, coffee powder, bean powder, washing powder, alkaline powder, organic fertilizer, etc..
- Worker put a large quantity of doypack pouches on the machine, machine automatic giving pouches.
- It with 6 stations, filling range from 100-1000ml, speed 2000-2500 pouches per hour..
- International electrical spare parts brand.
- All contact liquid parts are all SS304, machine body is SS304, machine frame is paint steel.

Main Function:

- Pouch-sending-printing date-opening-filling-forming-finished products conveying out.
- Machine is controlled by PLC + touch screen, automatic packing in whole process. High automation steady operation with the imported components, easy to repair and maintain.
- Adopt imported converter
- The machine has a special design for formed-working, which is enable to make no crimple by sealing head.
- Adopt spray plastic technical; configure imported stainless steel for the part of connection.
- Automatic counters according to the packing material's requirement.
- Automatic detect equipment, if the bag empty, bad or nonstandard that the machine will stop filling and sealing, fault alarm for heat equipment, automatic correct for sealing quantity blow the temperature.
- Adopt imported engineering plastic bearing, no need add oil, no need to repair, protecting for environment.

Technical Parameters:

Technical Parameters	
Bag style	Stand up pouches, Handbags, zipper bags, four sealed bags, three side sealed bags, paper bags, M-type bags and other composite bags
Bag material	PA/PE、 PET/PE、 aluminum heat sealed material
Bag size	W:70 ~ 200mm L: 100 ~ 300mm
Station process	1. feed bag 2. Code printing 3. Open the bag 4. filling 5. filling 6. Reserved 7. Heat sealing 8. Integer & output
Filling range	5 ~ 1500g(depends on different packing material)
Packing speed	20 ~ 60 bags per min,(depends on different weight or material)
Precision	≤±1%
Main machine weight	1000kg
Machine dimension	1570mm*1440mm*1480mm (L*W*H)
Main machine power	3kw